



Power cable ≥ 1 kV, for permanent installation

MarineWire Zp 0,6/1 kV

Article number: 160261

02-10-2026

Description

2,5 mm² Green/Yellow

Application:

MarineWire Zp 0,6/1 kV halogen-free earthing & power wires are used for wiring switchboards, control panels, and cabinets in all ship areas. Extra flexible Class 5/6 conductors for improved flexibility.

Characteristics (properties):

- Class 5/6 conductors, unarmoured
- Easy installation in tight spaces due to flexible conductors
- Halogen-free, low smoke, flame retardant insulation
- Green/Yellow sheath. Different colors on request
- DC voltage: 0,9/1,5 kV (if voltage to earth does not exceed 0,9 kV)

Core identification:

- HD308 S2



* This image may differ from the actual product.



Trading information

Product group	Power cable ≥ 1 kV, for permanent installation
Type	MarineWire Zp 0,6/1 kV
Net. Weight	0,031 kg/m
Sheath marking	{Length} TKF - MarineWire Zp - 0,6/1 kV - 2,5 mm ² - IEC 60332-3-22 Cat.A {Batch}

Trade lengths

Minimal order

Ring à 100	(160261R X 100 / 8713182397401)	1 PCE
------------	---------------------------------	-------



Power cable ≥ 1 kV, for permanent installation

MarineWire Zp 0,6/1 kV

Article number: 160261

02-10-2026

Construction characteristics

Standardization	IEC 60092-350/-360/-353
Number of cores	1
Nominal cross section conductor	2,5 mm ²
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 5 = flexible
Material core insulation	XLHFFR - HF90
Core colour	Green/Yellow
Colour insulated wires	Green/Yellow
Diameter conductor	2 mm
Insulation thickness	0,7 mm
Outer diameter approx.	3,4 mm

Properties

Flame retardant	IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
UV resistant	Yes
UV protection	NEN EN 50289-4-17A



Power cable ≥ 1 kV, for permanent installation

MarineWire Zp 0,6/1 kV

Article number: 160261

02-10-2026

Technical characteristics

Min. bending radius during installation	30 mm
Min. permitted bending radius, stationary application/permanent installation	15 mm
Tensile load	38 N
Max. permitted conductor temperature	90 °C
Transportation and storage temperature	-40 / 50 °C
Permitted cable outer temperature during assembling/handling	-20 / 50 °C
Permitted cable outer temperature after assembling without vibration	-40 / 90 °C

Electrical characteristics

Nominal voltage U ₀	0,6 kV
Nominal voltage U	1 kV
Test voltage	3,5 kV
Conductor DC resistance @ 20°C	7,98 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	10,18 Ohm/km