Power cable >= 1 kV, for permanent installation

# MarineLine+ YOZp 0,6/1 kV

Article number: 16186 | 02-10-2026

## Description

3 G 4 mm²

**Application:**

Armoured, heavy-duty, low voltage power cables for power and lighting applications in all ship areas.

**Characteristics (properties):**

- Class 2 conductors
- Extruded inner bedding for perfectly round shaped cable
- Halogen-free and low smoke, flame retardant
- Tinned copper wire braid armouring
- Perfect abrasion resistance & suitable for heavy-duty applications
- Different colour outer sheaths, other than black, available on request
- DC voltage: 0,9/1,5 kV (if voltage to earth does not exceed 0,9 kV)

**Core identification:**

- HD308 S2

PRODUCED WITH 100% GREEN ENERGY

* This image may differ from the actual product.

## Trading information

| | |
|---|---|
| Product group | Power cable >= 1 kV, for permanent installation |
| Type | MarineLine+ YOZp 0,6/1 kV |
| Net. Weight | 0,312 kg/m |
| Sheath marking | {Length} 0000 TKF - MarineLine+ YOZp 0,6/1 kV - 3G4 mm² +90 ° C - LSHF - IEC 60092-353, 60332-3-22 - {Batch} |

## Trade lengths

| | | Minimal order |
|---|---|---|
| | (16186 / 8713182063207) | 1000 MTR |
| Reel à 500 | (16186H X 500/20 / 8713182066093) | 2 PCE |
| Reel à 1000 | (16186H X 1000/30 / 8713182066079) | 1 PCE |

Power cable >= 1 kV, for permanent installation

# MarineLine+ YOZp 0,6/1 kV

Article number: 16186 | 02-10-2026

## Construction characteristics

| | |
|---|---|
| Standardization | IEC 60092-350/-360/-353 |
| Number of cores | 3 |
| Nominal cross section conductor | 4 mm² |
| Conductor material | Copper |
| Conductor surface | Bare |
| Standardization conductor material | IEC 60228 |
| Shape of conductor | Round |
| Conductor category | Class 2 = stranded |
| Material core insulation | Crosslinked polyethylene (XLPE) |
| Core identification | Colours and numbers |
| Conductor coding in accordance with HD 308 S2 | Yes |
| Colour insulated wires | Green/Yellow - Blue- Brown |
| Protective conductor | Yes |
| Screening | Yes |
| Construction outer shield | Tinned copper braiding |
| Binder/filler | FRNC filler |
| Material outer sheath | Flame Retardant Halogen Free Polyolefin Compound |
| Colour outer sheath | Black |
| Diameter conductor | 2,55 mm |
| Insulation thickness | 0,7 mm |
| Diameter shield wires | 0,2 mm |
| Diameter over braiding | 10,5 mm |
| Nominal outer sheath thickness | 1,2 mm |
| Outer diameter approx. | 12,9 mm |


Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl

Power cable >= 1 kV, for permanent installation

# MarineLine+ YOZp 0,6/1 kV

Article number: 16186 | 02-10-2026

## Properties

| | |
|---|---|
| Flame retardant | IEC 60332-1 / IEC 60332-3-22 Cat. A |
| Halogen free | IEC 60754-1/2 |
| Low smoke | IEC 61034-2 |
| UV resistant | Yes |
| UV protection | NEN EN 50289-4-17A |
| UV rating | Very good / Test duration >= 6000 h |

## Technical characteristics

| | |
|---|---|
| Min. bending radius during installation | 91 mm |
| Min. permitted bending radius, stationary application/permanent installation | 52 mm |
| Tensile load | 180 N |
| Max. permitted conductor temperature | 90 °C |
| Transportation and storage temperature | -40 / 50 °C |
| Permitted cable outer temperature during assembling/handling | -20 / 50 °C |
| Permitted cable outer temperature after assembling without vibration | -40 / 70 °C |


Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl

Power cable >= 1 kV, for permanent installation

# MarineLine+ YOZp 0,6/1 kV

Article number: 16186 | 02-10-2026

## Electrical characteristics

| | |
|---|---|
| Nominal voltage U0 | 0,6 kV |
| Nominal voltage U | 1 kV |
| Test voltage | 3,5 kV |
| Conductor DC resistance @ 20°C | 4,61 Ohm/km |
| Conductor AC resistance @ max. cont. Conductor temp. | 5,8 Ohm/km |
| Capacity | 45 nF/km |
| Inductance | 0,278 mH/km |


Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl