

Power cable ≥ 1 kV, for permanent installation

MarineFlex YOZp 0,6/1 kV

Article number: 16195

02-10-2026

Description

4 x 50 mm²

Application:


Lightweight, armoured, flexible low voltage power cables for power and lighting applications in all ship areas.

Characteristics (properties):

- Class 5 conductors
- Easy installation in tight spaces due to flexible conductors
- Halogen-free and low smoke, flame retardant
- Tinned copper wire braid armouring
- Excellent abrasion resistance
- Different colour outer sheaths, other than black, available on request
- DC voltage: 0,9/1,5 kV (if voltage to earth does not exceed 0,9 kV)

Core identification:

- HD308 S2



* This image may differ from the actual product.

Trading information

Product group	Power cable ≥ 1 kV, for permanent installation
Type	MarineFlex YOZp 0,6/1 kV
Net. Weight	2,823 kg/m
Sheath marking	{Length} 0000 TKF - MarineFlex YOZp 0,6/1 kV - 4x50 mm ² +90 ° C - LSHF - IEC 60092-353, 60332-3-22 - {Batch}

Trade lengths

Minimal order

	(16195 / 8713182053208)	1 MTR
Reel à 500	(16195H X 500/20 / 8713182053192)	1 PCE
Reel à 1000	(16195H X 1000/30 / 8713182053215)	1 PCE

Power cable ≥ 1 kV, for permanent installation

MarineFlex YOZp 0,6/1 kV

Article number: 16195

02-10-2026

Construction characteristics

Standardization	IEC 60092-350/-360/-353
Number of cores	4
Nominal cross section conductor	50 mm ²
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 5 = flexible
Material core insulation	Crosslinked polyethylene (XLPE)
Core identification	Colours and numbers
Conductor coding in accordance with HD 308 S2	Yes
Colour insulated wires	Blue - Brown - Black - Grey
Screening	Yes
Construction outer shield	Tinned copper braiding
Binder/filler	FRNC filler
Nominal equivalent cross section of reinforcement	19,6 mm ²
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Black
Diameter conductor	9 mm
Insulation thickness	1 mm
Diameter shield wires	0,3 mm
Diameter over braiding	29,9 mm
Nominal outer sheath thickness	1,9 mm
Outer diameter approx.	33,7 mm

Power cable ≥ 1 kV, for permanent installation

MarineFlex YOZp 0,6/1 kV

Article number: 16195

02-10-2026

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
UV resistant	Yes
UV protection	NEN EN 50289-4-17A
UV rating	Very good / Test duration ≥ 6000 h

Technical characteristics

Min. bending radius during installation	236 mm
Min. permitted bending radius, stationary application/permanent installation	135 mm
Tensile load	3.000 N
Max. permitted conductor temperature	90 °C
Transportation and storage temperature	-40 / 50 °C
Permitted cable outer temperature during assembling/handling	-20 / 50 °C
Permitted cable outer temperature after assembling without vibration	-40 / 70 °C



Power cable ≥ 1 kV, for permanent installation

MarineFlex YOZp 0,6/1 kV

Article number: 16195

02-10-2026

Electrical characteristics

Nominal voltage U_0	0,6 kV
Nominal voltage U	1 kV
Test voltage	3,5 kV
Conductor DC resistance @ 20°C	0,386 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	0,49 Ohm/km
Capacity	70 nF/km
Inductance	0,212 mH/km