



Power cable ≥ 1 kV, for permanent installation

MarineLine YOZp EMC 0,6/1 kV

Article number: 16541

02-10-2026

Description

12 G 2,5 mm²

Application:

Low voltage shipboard power cables with enhanced EMC properties for use in sensitive EMC areas and suitable for Variable Frequency Drive applications. Enhanced shielding properties due to optimized tinned copper wire braid in combination with 100% foil-screen coverage.

Characteristics (properties):

- Class 2 conductors
- Designed for situations that need Electro-Magnetic Interference to be limited to the minimum
- Halogen-free and low smoke, flame retardant
- Tinned copper wire braid armoring
- Different colour outer sheaths, other than black, available on request
- DC voltage: 0,9/1,5 kV (if voltage to earth does not exceed 0,9 kV)

Core identification:

- HD308 S2



* This image may differ from the actual product.

Trading information

Product group	Power cable ≥ 1 kV, for permanent installation
Type	MarineLine YOZp EMC 0,6/1 kV
Net. Weight	0,543 kg/m
Sheath marking	{Length} 0000 TKF - MarineLine YOZp EMC 0,6/1 kV - 12G2,5 mm ² +90 ° C - LSHF - IEC 60092-353, 60332-3-22 - {Batch}

Trade lengths

		Minimal order
	(16541 / 8713182262204)	1000 MTR
Reel à 500	(16541H X 500/20 / 8713182262211)	2 PCE

Power cable ≥ 1 kV, for permanent installation

MarineLine YOZp EMC 0,6/1 kV

Article number: 16541

02-10-2026

Construction characteristics

Standardization	IEC 60092-350/-360/-353
Number of cores	12
Nominal cross section conductor	2,5 mm ²
Conductor material	Copper
Conductor surface	Bare
Standardization conductor material	IEC 60228
Shape of conductor	Round
Conductor category	Class 2 = stranded
Material core insulation	Crosslinked polyethylene (XLPE)
Core identification	Colours and numbers
Conductor coding in accordance with HD 308 S2	Yes
Colour insulated wires	Green/Yellow - Black, with white printed numbers
Protective conductor	Yes
Screening	Yes
Construction outer shield	EMC-screen consists of Cu/PET-tape and tinned copper braiding
Binder/filler	Polyester tape
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Black
Diameter conductor	1,56 mm
Insulation thickness	0,7 mm
Diameter shield wires	0,3 mm
Diameter over braiding	14,7 mm
Nominal outer sheath thickness	1,4 mm
Outer diameter approx.	17,3 mm

Power cable ≥ 1 kV, for permanent installation

MarineLine YOZp EMC 0,6/1 kV

Article number: 16541

02-10-2026

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
UV resistant	Yes
UV protection	NEN EN 50289-4-17A
UV rating	Very good / Test duration ≥ 6000 h

Technical characteristics

Min. bending radius during installation	123 mm
Min. permitted bending radius, stationary application/permanent installation	70 mm
Tensile load	450 N
Max. permitted conductor temperature	90 °C
Transportation and storage temperature	-40 / 50 °C
Permitted cable outer temperature during assembling/handling	-20 / 50 °C
Permitted cable outer temperature after assembling without vibration	-40 / 70 °C

Electrical characteristics

Nominal voltage U_0	0,6 kV
Nominal voltage U	1 kV
Test voltage	3,5 kV
Conductor DC resistance @ 20°C	7,41 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	9,3 Ohm/km
Inductance	0,279 mH/km