



Single core single insulated wire ZDS H07Z-K 90°C Eca

Article number: 185706

02-10-2026

Description

1,5 mm² Black

Application:

Halogen-free internal wiring for switchboards, switchboxes and distribution systems in Marine, Offshore and Industrial Installations.
Extra flexible Class 5/6 conductors for improved flexibility.

Characteristics (properties):

- Halogen-free
- 450/750 V
- Suitable for continuous conductor temperature of 90°C
- KEMA-KEUR <HAR> (except for yellow and green colours)
- Lloyd's Register (LR) Type Approval
- EN 50525-2-31 and EN 50575



* This image may differ from the actual product.

Trading information

Product group	Single core single insulated wire
Type	ZDS H07Z-K 90°C Eca
Net. Weight	0,02 kg/m
Sheath marking	TKF - H07Z-K Eca DoP: DoP0022 [-CE-] 1,5 mm2 KEMA-KEUR [-HAR-] {Batch}

Trade lengths

		Minimal order
Ring à 100	(185706R X 100 / 8713182453107)	1 PCE
Reel à 500	(185706H X 500/20 / 8713182388393)	1 PCE



Single core single insulated wire
ZDS H07Z-K 90°C Eca

Article number: 185706

02-10-2026

Construction characteristics

Standardization	NEN EN 50525 / EN 50575
Number of cores	1
Nominal cross section conductor	1,5 mm ²
Conductor material	Copper
Conductor surface	Bare
Shape of conductor	Round
Conductor category	Class 5 = flexible
Standardization conductor material	IEC 60228
Material core insulation	Polyolefin
Core identification	Colour
Core colour	Black
Outer diameter approx.	3 mm

Properties

Flame retardant	According to IEC/EN 60332-1-2
Reaction-to-fire according to EN 13501-6: Class	Eca
Halogen free	IEC 60754-1 / IEC 60754-2
Low smoke	Yes
Weight	20 kg/km



Single core single insulated wire
ZDS H07Z-K 90°C Eca

Article number: 185706

02-10-2026

Technical characteristics

Min. permitted bending radius, stationary application/permanent installation	15 mm
Max. permitted conductor temperature	90 °C
Permitted cable outer temperature after assembling without vibration	-20 / 90 °C
Permitted cable outer temperature during assembling/handling	-5 / 55 °C

Electrical characteristics

Nominal voltage U0	450 V
Nominal voltage U	750 V
Test voltage	2,5 kV
Conductor DC resistance @ 20°C	13,3 Ohm/km