



Shipboard low voltage cable

MarineLine YZp FR 0,6/1 kV

Article number: 26063

18-08-2017

Description1 x 150 mm²

Fire resistant low voltage power cables for power and lighting applications in all ship areas, with reduced diameter and weight. High abrasion resistant sheath and easily strippable with ripcord. Halogen-free and low-smoke, flame-retardant in fire conditions.

**Trading information**

Product group	Shipboard low voltage cable
Series	Shipboard cable
Type	MarineLine YZp FR 0,6/1 kV
Net. Weight	1,534 kg/m
Sheath marking	{Length} TKF - 1X150 - 0,6/1 kV - CS 90 - mbzh - MarineLine YZp HALOGEN FREE - FIRE RESISTANT {Batch}

Trade lengths

Reel à 1	(26063 / 8713182112240)
Reel à 500	(26063H X 500/20 / 8713182112233)
Reel à 1000	(26063H X 1000/30 / 8713182112219)



Shipboard low voltage cable

MarineLine YZp FR 0,6/1 kV

Article number: 26063

18-08-2017

Construction characteristics

Standardization	IEC 60092-350/-360/-353
Standardization conductor material	IEC 60228
Standardization sheath material	IEC 60092-360
Number of cores	1
Conductor material	Cu
Shape of conductor	Round
Core insulation	Mica + XLPE
Conductor category	Class 2 = stranded
Core identification	HD 308 S2
Core lay-up	Concentric layers
Binder/filler	Polyester tape
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Orange

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Insulation integrity in accordance with IEC 60331	Yes
Nominal cross section conductor	150 mm ²
Outer diameter approx.	21.5 mm
Diameter conductor	15.72 mm
Insulation thickness	1.4 mm
Nominal outer sheath thickness	1.5 mm
Min. bending radius after installation	86 mm
Min. bending radius during installation	151 mm
Tensile load	2250 N



Shipboard low voltage cable

MarineLine YZp FR 0,6/1 kV

Article number: 26063

18-08-2017

Technical characteristics

Test voltage	3500 V
Nominal voltage U ₀	0.6 kV
Nominal voltage U	1 kV
Conductor DC resistance @ 20°C	0.124 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	0.16 Ohm/km
Inductance	0.193 mH/km
Maximum conductor temperature	90 °C
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C