



Shipboard low voltage cable

MarineLine YOZp FR 0,6/1 kV

Article number: 26157

26-07-2017

Description

3 x 95 svs

Fire resistant armoured, lightweight, reduced diameter low voltage cables for power and lighting applications in all ship areas where extra mechanical and EMC protection is needed. The sheath material has excellent abrasion resistance properties and can be stripped easily with the ripcord.

**Trading information**

Product group	Shipboard low voltage cable
Series	Shipboard cable
Type	MarineLine YOZp FR 0,6/1 kV
Net. Weight	3,273 kg/m
Sheath marking	{Length} TKF - 3X95 svs - 0,6/1 kV - CS 90 - mbzh - MarineLine YOZp FR HALOGEN FREE - FIRE RESISTANT {Batch}

Trade lengths

Reel à 1	(26157 / 8713182107598)
Reel à 500	(26157H X 500/20 / 8713182107581)
Reel à 1000	(26157H X 1000/30 / 8713182107567)



Shipboard low voltage cable

MarineLine YOZp FR 0,6/1 kV

Article number: 26157

26-07-2017

Construction characteristics

Standardization	IEC 60092-350/-360/-353
Standardization conductor material	IEC 60228
Standardization sheath material	IEC 60092-360
Number of cores	3
Conductor material	Cu
Shape of conductor	Sector-shaped
Core insulation	Mica + XLPE
Conductor category	Class 2 = stranded
Core identification	HD 308 S2
Core lay-up	Concentric layers
Binder/filler	Polyester tape
Screening	Yes
Construction outer shield	tinned copper braiding
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Orange



Shipboard low voltage cable

MarineLine YOZp FR 0,6/1 kV

Article number: 26157

26-07-2017

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Insulation integrity in accordance with IEC 60331	Yes
Nominal cross section conductor	95 mm ²
Outer diameter approx.	33.3 mm
Diameter conductor	15.8 mm
Insulation thickness	1.1 mm
Diameter over braiding	29.3 mm
Diameter shield wires	0.3 mm
Nominal outer sheath thickness	2 mm
Min. bending radius after installation	266 mm
Min. bending radius during installation	333 mm
Tensile load	4275 N

Technical characteristics

Test voltage	3500 V
Nominal voltage U ₀	0.6 kV
Nominal voltage U	1 kV
Conductor DC resistance @ 20°C	0.193 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	0.24 Ohm/km
Inductance	0.198 mH/km
Capacity	83 nF/km
Maximum conductor temperature	90 °C
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C