Shipboard low voltage cable

MarineLine YOZp FR 0,6/1 kV

Article number: 26183 | 26-07-2017

Description

21 x 2,5 mm2

Fire resistant armoured, lightweight, reduced diameter low voltage cables for power and lighting applications in all ship areas where extra mechanical and EMC protection is needed. The sheath material has excellent abrasion resistance properties and can be stripped easily with the ripcord.

Trading information

Product group	Shipboard low voltage cable
Series	Shipboard cable
Type	MarineLine YOZp FR 0,6/1 kV
Net. Weight	0,922 kg/m
Sheath marking	{Length} TKF - 21X2,5 - 0,6/1 kV - CS 90 - mbzh - MarineLine YOZp FR HALOGEN FREE - FIRE RESISTANT {Batch}

Trade lengths

Reel à 1	(26183 / 8713182233051)
Reel à 500	(26183H X 500/20 / 8713182233044)
Reel à 1000	(26183H X 1000/30 / 8713182233037)

Shipboard low voltage cable

MarineLine YOZp FR 0,6/1 kV

Article number: 26183 26-07-2017

Construction characteristics

Standardization	IEC 60092-350/-360/-353
Standardization conductor material	IEC 60228
Standardization sheath material	IEC 60092-360
Number of cores	21
Conductor material	Cu
Shape of conductor	Round
Core insulation	Mica + XLPE
Conductor category	Class 2 = stranded
Core identification	HD 308 S2
Core lay-up	Concentric layers
Binder/filler	Polyester tape
Screening	Yes
Construction outer shield	tinned copper braiding
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Colour outer sheath	Orange

Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl

Shipboard low voltage cable

MarineLine YOZp FR 0,6/1 kV

Article number: 26183 | 26-07-2017

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Insulation integrity in accordance with IEC 60331	Yes
Nominal cross section conductor	2.5 mm²
Outer diameter approx.	25.2 mm
Diameter conductor	2.04 mm
Insulation thickness	0.7 mm
Diameter over braiding	21.8 mm
Diameter shield wires	0.3 mm
Nominal outer sheath thickness	1.7 mm
Min. bending radius after installation	102 mm
Min. bending radius during installation	151 mm
Tensile load	788 N

Technical characteristics

Test voltage	3500 V
Nominal voltage U0	0.6 kV
Nominal voltage U	1 kV
Conductor DC resistance @ 20°C	7.41 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	9.3 Ohm/km
Inductance	0.279 mH/km
Maximum conductor temperature	90 °C
Permitted cable outer temperature, in movement	-20 / 70 °C
Permitted cable outer temperature, fixed	-40 / 70 °C

Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl