Data and communication cable

Marine2Com+ YOZ2c X-FR 250 V

Article number: 26738 | 02-10-2026

Description

8 x 2 x 1,5 mm²

* This image may differ from the actual product.

Trading information

Product group	Data and communication cable
Type	Marine2Com+ YOZ2c X-FR 250 V
Net. Weight	1,112 kg/m
Sheath marking	{Length} 0000 TKF - Marine2Com+ YOZ2c X-FR 250V - 8x2x1,5 mm² +90 ° C - LSHF - IEC 60092-376, 60332-3-22, 600331-1 {Batch}

Subject to technical modifications | No rights can be derived from this information

Data and communication cable

Marine2Com+ YOZ2c X-FR 250 V

Article number: 26738 | 02-10-2026

Construction characteristics

Standardization	IEC 60092-350/-360/-376
Number of cores	16
Nominal cross section conductor	1,5 mm²
Conductor material	Copper
Conductor surface	Bare
Conductor category	Class 2 = stranded
Standardization conductor material	IEC 60228
Number of stranding elements	8
Number of conductors per group	2
Screen over stranding element	Aluminium polyester tape
Core lay-up	Concentric layers
Material core insulation	Mica + XLHFFR
Core identification	Numbers
Binder/filler	FRNC filler
Screen over stranding	Foil + braiding
Construction outer shield	Tinned copper braiding
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Standardization sheath material	IEC 60092-360
Colour outer sheath	Orange

Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl

Data and communication cable

Marine2Com+ YOZ2c X-FR 250 V

Article number: 26738 | 02-10-2026

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Fire resistant	IEC 60331-1/2
Flame retardant according to IEC 60332-3-22 (Cat A)	Yes
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
UV resistant	Yes
UV protection	NEN EN 50289-4-17A
UV rating	Limited / Test duration 720 <= h <2000
Diameter conductor	1,56 mm
Insulation thickness	0,7 mm
Diameter shield wires	0,3 mm
Diameter over braiding	23,2 mm
Nominal outer sheath thickness	1,7 mm
Outer diameter approx.	26,6 mm

Technical characteristics

Min. bending radius during installation	266 mm
Min. permitted bending radius, stationary application/permanent installation	213 mm
Tensile load	360 N
Max. permitted conductor temperature	90 °C
Permitted cable outer temperature during assembling/handling	-20 / 50 °C
Permitted cable outer temperature after assembling without vibration	-40 / 70 °C
Transportation and storage temperature	-40 / 50 °C

Data and communication cable

Marine2Com+ YOZ2c X-FR 250 V

Article number: 26738 | 02-10-2026

Electrical characteristics

Nominal voltage U	250 V
Test voltage	1.500 V
Conductor DC resistance @ 20°C	12,8 Ohm/km
Conductor AC resistance @ max. cont. Conductor temp.	16,3 Ohm/km
Capacity	110 nF/km
Inductance	0,307 mH/km

Subject to technical modifications | No rights can be derived from this information

Spinnerstraat 15 | P.O. Box 6 | 7481 KJ Haaksbergen | Nederland | Phone: +31 (0)53 573 22 55 | E-mail: info@tkf.nl