



Medium-voltage ship-cable

MarinePower YOZmv 6/10 kV

Article number: 33099

02-10-2026

Description1 x 25 mm²**Application:**

Heavy duty, midvoltage (6/10 kV), armoured power cables, designed for medium voltage energy transport for fixed installation in all ship areas. The cable is compliant with the specifications of VFD manufacturers.

Characteristics (properties):

- Class 2 conductor, with special XLPE insulation
- Excellent mechanical and EMC protection due to the tinned copper braid
- Halogen free and low smoke, flame retardant
- Excellent abrasion resistance
- Different colour outer sheaths, other than red, available on request



* This image may differ from the actual product.

Trading information

Product group	Medium-voltage ship-cable
Type	MarinePower YOZmv 6/10 kV
Net. Weight	0,605 kg/m
Sheath marking	{Length} TKF - 6/10kV - 1x25rs CS90 mbzh MarinePower YOZmv HALOGEN FREE {Batch}

Trade lengths

Minimal order

	(33099 / 8713182258528)	1000 MTR
Reel à 500	(33099H X 500/20 / 8713182258535)	2 PCE





Medium-voltage ship-cable

MarinePower YOZmv 6/10 kV

Article number: 33099

02-10-2026

Construction characteristics

Standardization	IEC 60092-354
Number of cores	1
Nominal cross section conductor	25 mm ²
Conductor material	Cu
Shape of conductor	Round
Conductor category	K1.2+ = stranded flexible
Conductor shield	Semiconductive Compound
Material core insulation	Crosslinked polyethylene (XLPE)
Insulation shield	Semiconductive XLPE, semiconductive tape and braiding
Earthscreen construction	Tinned copper braiding
Insulation thickness	3,4 mm
Armouring	Yes
Material outer sheath	Flame Retardant Halogen Free Polyolefin Compound
Outer diameter approx.	20,1 mm
Colour outer sheath	Red

Properties

Flame retardant	IEC 60332-1 / IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1/2
Low smoke	IEC 61034-2
Min. bending radius after installation	0,16 m
Min. bending radius during installation	0,24 m
Tensile load	1.250 N



Medium-voltage ship-cable

MarinePower YOZmv 6/10 kV

Article number: 33099

02-10-2026

Technical characteristics

Conductor DC resistance @ 20°C	0,727 Ohm/km
Minimum installation temperature	-5 °C
Max. operating temperature	70 °C
Max. permitted conductor temperature	90 °C
Permitted cable outer temperature during assembling/handling	-20 / 50 °C
Permitted cable outer temperature after assembling without vibration	-40 / 70 °C
Transportation and storage temperature	-40 / 50 °C

Electrical characteristics

Nominal voltage U0	6 kV
Nominal voltage U	10 kV
Nominal voltage Umax	12 kV